



## EDL-430/WS

Order No.: 0162370

### PRODUCTINFOS

#### Top-quality PA ball speaker,

with a perfect omnidirectional sound radiation.

- 100 V transmission technology
- High-performance full range speaker
- Extensive reflector design
- Great speech intelligibility
- White ABS housing
- 150 cm connection cable with canopy

### TECHNICAL SPECIFICATIONS

#### EDL-430/WS

Active/passive	passive
Transmission technology	100 V
Total power rating	20 W
Power rating (RMS)	20/10/5 W

**EDL-430/WS**

Frequency range	80-15,000 Hz
Number of speakers	1
Speaker size	20 cm (8")
SPL	92 dB/W/m
Radiation angle/beam angle	360°
Radiation angle, horizontal	360°
Housing material	ABS
Colour	white
Mounting device	mounting hook/canopy
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 250 mm
Width	Ø 250 mm
Height	Ø 250 mm
Depth	Ø 250 mm
Weight	2.3 kg
Inputs	cable connection
Packaging dimensions (W x H x L)	0.32 x 0.31 x 0.32 m
Gross weight	3.22 kg
Net weight	2.34 kg

**EDL-430/WS**

EAN code	4007754203332
Net weight	2.34 kg