



## EDL-530EN/SW

Order No.: 1000261

### PRODUCTINFOS

#### High-quality PA pendant speaker,

with EN 54-24 certification.

- 100 V transmission technology or 8  $\Omega$  operation
- 2-way coaxial system (5.25")
- UV-resistant ABS housing with aluminium grille
- Excellent sound quality for speech and music
- 5 m safety rope
- Plug-in screw terminal

### TECHNICAL SPECIFICATIONS

#### EDL-530EN/SW

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	30 W
Power rating (RMS)	30/15/7.5/3.8 W

**EDL-530EN/SW**

Impedance	8 $\Omega$
Frequency range	65-20,000 Hz
System	2-way coaxial
Bass speaker	13.33 cm (5.25")
Tweeter	25 mm (1")
Number of speakers	2
Speaker size	13.33 cm (5.25")
SPL	90 dB/W/m
Radiation angle/beam angle	120°
Radiation angle, horizontal	120°
Radiation angle, vertical	120°
Housing material	ABS
Colour	black
Mounting device	Eyelet bolt and 5 m steel rope with snap hook
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 195 mm x 250 mm
Width	Ø 195 mm
Height	250 mm
Depth	Ø 195 mm
Weight	2.26 kg
Inputs	plug-in screw terminal
Packaging dimensions (W x H x L)	0.22 x 0.3 x 0.22 m
Gross weight	2.66 kg
Net weight	2.26 kg