



RL-1ENABDS

Order No.: 0163690



PRODUCTINFOS

PA A/B sound projector for wall mounting,

with EN 54-24 certification for voice evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 13 cm full range speaker with dual voice coil
- 2 x 100 V transformer with power taps on the cable 6/3/1.5 W
- Connection via 2 x 4-core cable (length: 1.5 m)
- Metal housing with front protective grille
- Supplied with pan/tilt bracket and mounting accessories

TECHNICAL SPECIFICATIONS

RL-1ENABDS

Active/passive	passive
Transmission technology	100 V
Power rating (RMS)	2 x 6/3/1.5 W

RL-1ENABDS

Frequency range	80-20,000 Hz
Full range speaker	13 cm, dual voice coil
Speaker size	13 cm
SPL	93 dB/W/m
Max. rated SPL	101 dB
Radiation angle/beam angle	130°
Radiation angle, horizontal	130°
Radiation angle, vertical	130°
Housing material	aluminium
Colour	white
Mounting device	bracket
Admiss. ambient temp.	-10 °C to +55 °C
Dimensions	Ø 144 mm x 210 mm
Width	Ø 144 mm
Depth	210 mm
Weight	2.3 kg
Packing dimensions (W x H x L)	0.185 x 0.285 x 0.185 m
Gross weight	2.51 kg
Net weight	2.32 kg