



## ESP-50AB/WS

Order No.: 16.0120

**Price upon request**

### PRODUCTINFOS

#### **PA A/B wall speaker,**

with EN 54-24 certification for evacuation systems with A/B speaker distribution according to EN 60849 and DIN VDE 0833-4.

- 100 V line technique
- 2 separate full range speakers (10 cm), each with its own transformer 6/3/1.5 W
- Connection via 2 spring-loaded terminals inside the cabinet
- Wooden cabinet with protective metal grille
- Easy wall mounting via supplied metal bracket and mounting accessories
- Ball-proof according to DIN 18032, Part 3

### TECHNICAL SPECIFICATIONS

#### **ESP-50AB/WS**

Active/passive	passive
Transmission method	100 V

**ESP-50AB/WS**

Power rating (RMS)	2 x 6/3/1.5 W
Frequency range	120-20,000 Hz
Number of speakers	2
Speaker size	10 cm
Sensitivity	92 dB/W/m
Max. rated SPL	99 dB
Housing material	wood
Colour	white
Mounting device	metal bracket
Protected against ball rebound	yes
Admiss. ambient temp.	-10 °C to +50 °C
Dimensions	265 x 165 x 90 mm
Width	265 mm
Height	165 mm
Depth	90 mm
Weight	1.9 kg