



ESP-50AB/WS



Order No.: 0160120

PRODUCTINFOS

PA A/B wall speaker,

with EN 54-24 certification for voice evacuation systems with A/B speaker distribution according to EN 60849 and DIN VDE 0833-4.

- 100 V line technique
- 2 separate full range speakers (10 cm), each with its own transformer 6/3/1.5 W
- Connection via 2 spring-loaded terminals inside the cabinet
- Wooden cabinet with protective metal grille
- Easy wall mounting via supplied metal bracket and mounting accessories
- Ball-proof according to DIN 18032, Part 3

TECHNICAL SPECIFICATIONS

ESP-50AB/WS

Active/passive	passive
Transmission technology	100 V
Power rating (RMS)	2 x 6/3/1.5 W

ESP-50AB/WS

Frequency range	120-20,000 Hz
Number of speakers	2
Speaker size	10 cm
SPL	92 dB/W/m
Max. rated SPL	99 dB
Housing material	wood
Colour	white
Mounting device	metal bracket
Protected against ball rebound	yes
Admiss. ambient temp.	-10 °C to +50 °C
Dimensions	265 x 165 x 90 mm
Width	265 mm
Height	165 mm
Depth	90 mm
Weight	1.9 kg
Packing dimensions (W x H x L)	0.18 x 0.27 x 0.1 m
Gross weight	2.12 kg
Net weight	1.9 kg