



ESP-1000AB



Order No.: 0163670

PRODUCTINFOS

PA A/B wall speaker,

with EN 54-24 certification for voice evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 2 x 10 cm full range speaker
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Plastic cabinet with open rear panel with protective metal front grille
- Supplied with aluminium mounting bracket, screws and wall plugs

TECHNICAL SPECIFICATIONS

ESP-1000AB

Active/passive	passive
Transmission technology	100 V
Power rating (RMS)	2 x 6/3/1.5 W

ESP-1000AB

Frequency range	80-20,000 Hz
Full range speaker	2 x 10 cm
Number of speakers	2
Speaker size	10 cm
SPL	92 dB/W/m
Max. rated SPL	100 dB
Radiation angle/beam angle	160°
Radiation angle, horizontal	160°
Radiation angle, vertical	160°
Housing material	metal
Colour	white
Mounting device	bracket
Admiss. ambient temp.	-10 °C to +50 °C
Dimensions	Ø 220 mm x 100 mm
Width	Ø 220 mm
Depth	100 mm
Weight	1.98 kg
Packing dimensions (W x H x L)	0.235 x 0.125 x 0.235 m
Gross weight	2.126 kg
Net weight	1.986 kg