



DA-10-260/T

Order No.: 0163710

PRODUCTINFOS

The sound projector with a power capacity of 10 W is fitted with two 13 cm full range speakers and a 100 V transformer with 4 power taps. A robust plastic-coated aluminium housing in RAL9010 and a vandal-resistant aluminium mounting plate ensure a permanent installation of this speaker. The 2-pole ceramic terminal and thermal fuse as well as the waterproof speaker ensure extra operating reliability.

With the high protection class IP65, the speaker is also protected against weather influences. It is particularly suitable for the application in corridors and hallways. The speaker complies with British Standard BS 5839, Part 8.

Weatherproof PA sound projector,

for wall mounting and with EN 54-24 certification.

- 100 V line technique
- 2 x 13 cm full range speaker for bi-directional radiation
- 100 V transformer with power taps 10/6/3/1.5 W
- Connection via ceramic terminals with thermal fuse in the mounting base
- Robust plastic-coated aluminium housing with front protective grille
- Robust vandal-resistant aluminium mounting base

TECHNICAL SPECIFICATIONS

DA-10-260/T

Active/passive	passive
Transmission technology	100 V
Power rating (RMS)	10/6/3/1.5 W
Frequency range	120-17,000 Hz
Full range speaker	2 x 13 cm
Number of speakers	2
Speaker size	13 cm
SPL	93 dB/W/m
Max. rated SPL	103 dB
Radiation angle/beam angle	150°
Radiation angle, horizontal	150°
Radiation angle, vertical	150°
Housing material	aluminium
Colour	white, RAL 9010
Mounting device	mounting base
Protection class	IP65
Admiss. ambient temp.	-20 °C to +90 °C
Dimensions	166 x 197 x 161 mm
Width	166 mm
Height	197 mm
Depth	161 mm
Weight	2.31 kg
Packing dimensions (W x H x L)	0.17 x 0.185 x 0.21 m
Gross weight	2.43 kg
Net weight	2.31 kg