



DA-P20-130/T

Order No.: 0163880

PRODUCTINFOS

Weatherproof PA sound projector,

for wall mounting and with EN 54-24 certification.

- 100 V line technique
- 13 cm waterproof full range speaker
- 100 V transformer with power taps 20/10/5/2.5 W
- Connection via ceramic terminal and thermal fuse in the junction box (cable length: 1 m)
- ABS plastic housing with front protective grille
- Robust aluminium mounting bracket

TECHNICAL SPECIFICATIONS

DA-P20-130/T

Active/passive	passive
Transmission method	100 V
Power rating (RMS)	20/10/5/2.5 W
Frequency range	150-20,000 Hz

DA-P20-130/T

Full range speaker	13 cm
Number of speakers	2
Speaker size	13 cm
Sensitivity	90 dB/W/m
Max. rated SPL	104 dB
Beam angle	110°
Radiation angle, horizontal	110°
Radiation angle, vertical	110°
Housing material	ABS plastic
Colour	white
Mounting device	bracket
Protection class	IP66
Admiss. ambient temp.	-20 °C to +90 °C
Dimensions	Ø 145 mm x 222 mm
Width	Ø 145 mm
Depth	222 mm
Weight	1.367 kg
Packing dimensions (W x H x L)	0.175 x 0.295 x 0.18 m
Gross weight	1.625 kg
Net weight	1.367 kg