



## ESP-230/WS

Order No.: 0190010

### PRODUCTINFOS

#### Weatherproof PA speaker system,

in a white plastic cabinet with protective aluminium grille.

- 100 V line technique
- Hose-proof
- Switchable to 8  $\Omega$  operation
- 5 power taps, 8  $\Omega$  connection and 100 V power selector switch
- 2-way system
- Stainless steel mounting bracket

### TECHNICAL SPECIFICATIONS

#### ESP-230/WS

|                         |         |
|-------------------------|---------|
| Active/passive          | passive |
| Transmission technology | 100 V   |
| Total power rating      | 100 W   |

**ESP-230/WS**

Power rating (RMS) 30/20/10/5/2.5 W (100 V)

50 W (8  $\Omega$ )

Impedance 8  $\Omega$

Frequency range 80-20,000 Hz

System 2-way

Number of speakers 2

SPL 92 dB/W/m

Housing material plastic

Colour white

Mounting device mounting bracket

Protection class IP65

Admiss. ambient temp. -30 °C to +40 °C

Dimensions 157 x 260 x 170 mm

Width 157 mm

Height 260 mm

Depth 170 mm

Weight 1.8 kg

Inputs spring-load. speaker term.

Packing dimensions (W x H x L) 0.2 x 0.29 x 0.2 m

Gross weight 2.276 kg

Net weight 2 kg