



IT-10M

Order No.: 0160470

PRODUCTINFOS

Flush-mount horn speaker (music horn) with full range speaker

- For wall mounting and ceiling installation
- 100 V line technique with 3 power taps
- After installation weatherproof and IP54 certified
- 5 cm (2.5") full range speaker with horn front attachment
- Suitable for general indoor and outdoor applications wherever a high sound pressure level and an excellent sound are required
- ABS plastic housing
- Mounting flange with foam rubber sealing

TECHNICAL SPECIFICATIONS

IT-10M

Active/passive	passive
Transmission technology	100 V
Total power rating	10 W

IT-10M

Power rating (RMS)	10/5/2.5 W
Frequency range	200-15,000 Hz
Number of speakers	1
SPL	98 dB/W/m
Beam angle	H: 100°/V: 100°
Radiation angle, horizontal	100°
Radiation angle, vertical	100°
Features	full range speaker
Housing material	ABS
Colour	grey
Mounting device	mounting flange with foam rubber seal
Protection class	IP54
Admiss. ambient temp.	0-40 °C
Dimensions	120 x 120 x 120 mm mounting cutout: Ø 101 mm
Width	120 mm
Height	120 mm
Depth	120 mm
Weight	0.75 kg
Other features	weatherproof
Packing dimensions (W x H x L)	0.15 x 0.125 x 0.155 m
Gross weight	0.84 kg
Net weight	0.761 kg