



TS-C30-700/T

Order No.: 0163720

PRODUCTINFOS

Weatherproof PA column speaker,

with EN 54-24 certification.

- 100 V line technique
- 6 x 7.7 cm (3") waterproof full range speaker
- 3 power taps: 30/15/7.5 W
- Connection via ceramic terminals with thermal fuse in the cabinet
- 2 x PG9 cable gland
- Robust, plastic-coated aluminium cabinet with front protective grille
- The speaker complies with British Standard BS 5839, part 8
- Supplied with plastic wall bracket for pivoting and tilting

TECHNICAL SPECIFICATIONS

TS-C30-700/T

Active/passive	passive
Transmission method	100 V

TS-C30-700/T

Power rating (RMS)	30/15/7.5 W
Frequency range	200-17,000 Hz
Full range speaker	6 x 77 mm
Number of speakers	6
Sensitivity	97 dB/W/m
Max. rated SPL	109 dB
Beam angle	H: 160°/V: 26°
Radiation angle, horizontal	160°
Radiation angle, vertical	26°
Housing material	aluminium
Colour	white aluminium, RAL 9006
Mounting device	wall bracket
Protection class	IP66
Admiss. ambient temp.	-20 °C to +90 °C
Dimensions	100 x 700 x 92 mm
Width	100 mm
Height	700 mm
Depth	92 mm
Weight	3.8 kg