



PAB-6WP/WS

Order No.: 0253560

PRODUCTINFOS

Weatherproof PA speakers with IP classification.

Exactly the right speakers whenever a high sound quality, a high volume capability and a respective resistance to all weather conditions are required. Ideally suited for permanent open-air applications, e.g. at fairground attractions, PA applications in pedestrian areas, at sports facilities and wherever a weather-protected installation of the speakers is not possible.

Weatherproof high-performance PA speaker system, 100 W

- Compact 2-way bass-reflex system in an ABS cabinet
- 100 V or 8 Ω operation, selectable
- 16 cm bass speaker with coated carbon fibre cone
- 30 mm dome tweeter with horn front attachment
- Front grille with water-repellent gauze
- Recessed connection terminal with cover plate and high-strength cable gland
- Metal parts and wall bracket made of stainless steel
- Ball-proof according to DIN 18032, Part 3

“The cabinets give a solid impression ... and meet IP45 requirements. All four speaker systems are suitable for pleasant background music ... the large PAB-8WP/WS is capable of quite high volume levels ... however, the small ones should not be underestimated ... these speaker systems are impressive and the price is quite reasonable for weatherproof speaker systems.”

TECHNICAL SPECIFICATIONS

PAB-6WP/WS

| | |
|--------------------------------|----------------------|
| Active/passive | passive |
| Transmission method | 100 V |
| Total power rating | 180 W |
| Power rating (RMS) | 100/50/25 W |
| Impedance | 8 Ω |
| Frequency range | 42-19,000 Hz |
| System | 2-way bass-reflex |
| Bass speaker | 16 cm bass speaker |
| Tweeter | 30 mm dome |
| Number of speakers | 2 |
| Speaker size | 16 cm |
| Sensitivity | 90 dB/W/m |
| Max. rated SPL | 110 dB |
| Housing material | ABS plastic |
| Colour | white |
| Mounting device | mounting bracket |
| Protected against ball rebound | yes |
| Protection class | IP45 |
| Admiss. ambient temp. | -10 °C to +40 °C |
| Dimensions | 200 x 370 x 240 mm |
| Width | 200 mm |
| Height | 370 mm |
| Depth | 240 mm |
| Weight | 7.1 kg |
| Inputs | screw terminal |
| Packing dimensions (W x H x L) | 0.31 x 0.47 x 0.24 m |
| Gross weight | 8.42 kg |
| Net weight | 7.68 kg |