



PA-4000RC

Order No.: 0236010

PRODUCTINFOS

PA 4-zone paging desktop microphone,

for connection to PA-40120 and PA-6040MPX.

- Selection buttons for 4 zones, for activating one or several zones
- ALL CALL button for activating all of the 4 zones
- Autom. chime via microphone announcement button (talk)
- LED status indication for the zone buttons (busy, emergency), power, mic fault, signal and talk
- Built-in gooseneck electret microphone
- Adjustable microphone sensitivity
- Chime can be activated or deactivated as required
- 24 V power supply via PA-40120 or PA-6040MPX
- Two RJ45 jacks for connection to PA-40120, PA-6040MPX or optional power supply and additional microphones PA-4000RC
- Supplied with connection module for PA-40120 and PA-6040MPX
- Up to 32 x PA-4000RC can be connected to PA-40120 or PA-6040MPX via bus
- Supplied with 3 m connection cable (Cat. 5e)

TECHNICAL SPECIFICATIONS

PA-4000RC

Description	PA desktop microphone
Transmission method	cable
Polar pattern	omnidirectional
Power supply	via PA-40120, PA-6040MPX or optional 24 V power supply
Admiss. ambient temp.	0-40 °C
Weight	0.9 kg
Cable	Cat. 5e, 3 m
Connection	2 x RJ45
Packing dimensions (W x H x L)	0.16 x 0.18 x 0.375 m
Gross weight	1.202 kg
Net weight	0.9 kg