



SA-100

Order No.: 0254120

PRODUCTINFOS

Compact universal stereo amplifier, 50 W

- Silent operation due to fanless cooling concept
- Additional 3.5 mm connection with switchable sensitivity on the front panel
- USB port on the front panel for power supply and for charging external devices
- Audio source selector switch
- Controls for volume, bass and treble
- 6.3 mm headphone output
- Robust metal housing

TECHNICAL SPECIFICATIONS

SA-100

| | |
|---------------------|------------------------------------------------------------------|
| Peak output power | 2 x 50 W |
| Power rating | 50 W |
| Power rating at 4 Ω | 2 x 25 W |
| Power rating at 8 Ω | 2 x 20 W |
| Channels | 2 |
| Inputs | 140 mV/46 kΩ (PC, CD, aux) 140 mV/12 kΩ, 25 mV/32 kΩ (player) |

SA-100

| | |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Frequency range | 20-20,000 Hz |
| Equalizer bass | ± 12 dB |
| Equalizer treble | ± 12 dB |
| S/N ratio | > 70 dB |
| Power supply | ~ 230 V/50 Hz/150 VA |
| Mains voltage | ~ 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 150 VA |
| Admiss. ambient temp. | 0-40 °C |
| Width | 212 mm |
| Height | 56 mm |
| Depth | 250 mm |
| Weight | 2.6 kg |
| Connections | 1 x RCA L/R (PC), 1 x RCA L/R (CD), 1 x RCA L/R (aux), 1 x 3.5 mm jack (player), 4 x spring-load. speaker term. (speakers) |
| Packing dimensions (W x H x L) | 0.315 x 0.105 x 0.315 m |
| Gross weight | 3.11 kg |
| Net weight | 2.6 kg |