



# PA-1200

Order No.: 0170710

## PRODUCTINFOS

### 4-zone mono PA mixing amplifier

- 1 x 120 W
- Silent operation due to fanless cooling concept
- Chime, continuous sound and wailing sound, automatic mute, chime can also be activated via external momentary push-button, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs
- 15 V phantom power for channels 2 and 3
- Insertions for various functions are available at option
- 482 mm (19") rack installation with mounting frame PA-1200RM, available at option
- Mains operation and 24 V emergency power operation

## TECHNICAL SPECIFICATIONS

### PA-1200

Peak output power	170 W
Power rating	120 W
Channels	5
Zones	4

**PA-1200**

Inputs	1.5 mV/600 $\Omega$ (mic), 150 mV/47 k $\Omega$ (line), 1 mV/47 k $\Omega$ (phono)
Frequency range	80-15,000 Hz
Equalizer bass	$\pm 10$ dB/100 Hz
Equalizer treble	$\pm 10$ dB/10 kHz
S/N ratio	> 60 dB (mic), > 70 dB (line)
THD	< 1%
Phantom power	15 V
Power supply	~ 230 V/50 Hz/280 VA, DC 24 V/11 A
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	280 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 11 A
Admiss. ambient temp.	0-40 °C
Width	420 mm
Height	122 mm
Depth	350 mm
Weight	12.28 kg
Connections	1 x 6.3 mm jack (mic input), 3 x XLR, bal. (mic/line inputs), 1 x RCA L + R (line input), 1 x RCA L + R (phono/line input), spring-load. contact (telephone input), spring-load. contact (tuner output), spring-load. contact (chime button), screw contacts (speakers)
Packing dimensions (W x H x L)	0.47 x 0.2 x 0.52 m
Gross weight	13.8 kg
Net weight	12.28 kg