



AKB-160DT



Order No.: 0176070

PRODUCTINFOS

Let's stream ...

The well-known and reliable amplifier systems PA-900 and AKB-160 now feature a 2-channel Dante® module which turns them into Dante® instreamers for versatile applications. They are able to receive one digital stereo signal or two mono signals via the RJ45 connections. These signals are converted into an analogue audio signal, amplified and then streamed. Thus, it is possible to integrate an analogue speaker system into a digital Dante® network.

PA amplifier module with integrated Dante® module

- 1 x 40 W
- 100 V output
- Silent operation due to fanless cooling concept
- Dante® input
- Speaker output via screw terminal
- Metal housing with mounting brackets

System requirements Dante®: Windows 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

What is the maximum current consumption in standby mode?

The current consumption in standby mode is approx. 30 mA.

TECHNICAL SPECIFICATIONS

AKB-160DT

Peak output power	60 W
Power rating	40 W
Power rating at 100 V	40 W
Channels	1
Zones	1
Inputs	network
Frequency range	17-20,000 Hz
S/N ratio	> 80 dB
THD	< 1%
Power supply	~ 230 V/50 Hz/75 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	75 VA
Admiss. ambient temp.	0-40 °C
Width	213 mm
Height	55 mm
Depth	238 mm
Weight	3.2 kg
Connections	1 x RJ45 (Dante®)
Packaging dimensions (W x H x L)	0.31 x 0.11 x 0.29 m
Gross weight	3.68 kg
Net weight	3.27 kg