



## ATS-22T

Order No.: 0257120

### PRODUCTINFOS

#### **16-channel Digital Voice Transmission System, 863-865 MHz**

- Suitable as a tour guide system, trainer/student system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- Parallel operation of up to 4 different channels possible without any interference
- Licence-free in the EU

#### **16-channel miniature transmitter,**

for microphone operation and audio line signals, with intercom function.

- Supplied with headset
- Activation switch for intercom function with the receiver ATS-22R
- Audio line input via 3.5 mm jack at the headset
- LCD for indicating channel and battery status
- Mute button
- Transmitting power:  $\leq 10$  mW (EIRP), operating range: approx. 70 m
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)

- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 80 x 12 mm
- Weight: 37 g

**Licence-free in the EU.**

## TECHNICAL SPECIFICATIONS

### ATS-22T

#### General information

Description	16-channel digital miniature transmitter
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C

#### Specifications transmitter

Transmitting power	$\leq 10$ mW
Operating range	70 m
Power supply transmitter	integrated rech. lithium batt. (3.7 V/600 mAh)
Width transmitter	40 mm
Height transmitter	80 mm
Depth transmitter	12 mm
Weight transmitter	37 g
Connections transmitter	3.5 mm jack (microphone/line in), micro USB charging port